

SPLIT INDOOR UNIT (1Ø 230V, 3Ø 400V)



Hydrokit _ Indoor Unit		HN0914. NK1	*HN0916. NK1	*HN0926. NK1	*HN0936. NK1	HN1616. NK1	HN1626. NK1	HN1636. NK1	*HN1629. NK1	HN1639. NK1
Combined Outdoor Unit		HU0914U41 - 1ø 230V				HU121U31 - 1ø 230V HU141U31 - 1ø 230V HU161U31 - 1ø 230V  HU123U31 - 3ø 400V HU143U31 - 3ø 400V HU163U31 - 3ø 400V				
Electric Heater	Power Supply	1ø/220-240V/50Hz		1ø/220-240V/50Hz		1ø/220-240V/50Hz		3ø/380-415V/50Hz		3ø/380-415V/50Hz
Heater	Capacity	4		6		6		9		9
Dimension	W*H*PD	mm		430*850*315		430*850*315		430*850*315		430*850*315
Weight		kg		48		54.5		54.5		54.5
Noise Level at 1 meter		dB(A)		28		28		28		28
Leaving Water Temperature	Heating	°C		15-55		15-55		15-55		15-55
	Cooling	°C		6-30		6-30		6-30		6-30
Water Pump	Max. Power Input	Watt		135		205		205		205
	Minimum Water Flow Rate	LPM		15		15		15		15
Max. Head		meter		6		7		7		7
Expansion Tank		liter		8		8		8		8

SPLIT OUTDOOR UNIT (1Ø 230V)



Outdoor Unit		HU091.L.041	
Combined Hydrokit		HN0916. NK1 HN0926. NK1 HN0936. NK1 HN0914. NK1	
Power Supply	ø/ V / Hz	1ø / 220-240V / 50Hz	
Nominal Capacity	Heating(A10/W35)	kW	9.71
	Heating(A7/W35)	kW	9
	Heating(A2/W35)	kW	6.87
	Heating(A-7/W35)	kW	8.61
	Cooling(A35/W18)	kW	9.00
Nominal Input	Heating(A10/W35)	kW	2.2
	Heating(A7/W35)	kW	2.07
	Heating(A2/W35)	kW	3.19
	Heating(A-7/W35)	kW	2.65
	Cooling(A35/W18)	kW	2.65
COP	Heating(A10/W35)	WW	4.41
	Heating(A7/W35)	WW	4.09
	Heating(A2/W35)	WW	3.32
	Heating(A-7/W35)	WW	2.70
EER	Cooling(A35/W18)	WW	3.40
Sound pressure level	Heating	dBA	52
	Cooling	dBA	52
Dimension	W*H*PD	mm	952*494*330
Weight		kg	54
Refrigerant (R410A)	Pre-charged amount	g	1,000
	Pipe Diameter(Liquid/Gas)	inch	3/8, 5/8