

INDOOR UNIT SPECIFICATION

ARTCOOL GALLERY

ARNU07GSF14 / ARNU09GSF14 / ARNU12GSF14



Model	Independent Unit			ARNU07GSF14	ARNU09GSF14	ARNU12GSF14
Capacity	Cooling	Nom	kW	2.2	2.8	3.6
	Heating	Nom	kW	2.5	3.2	4.0
Power Input	Cooling / Heating	Nom ¹⁾	W	28	28	35
	Cooling / Heating	Rated ²⁾	W	35	35	35
Power Supply			Ø / V / Hz	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L	m ³ /min	8.1 / 6.3 / 4.2	8.1 / 6.3 / 4.2	9.3 / 7.7 / 6.0
	Heating	H / M / L	m ³ /min	8.1 / 6.3 / 4.2	8.1 / 6.3 / 4.2	9.3 / 7.7 / 6.0
Sound Pressure			H / M / L dBA	38 / 32 / 27	38 / 32 / 27	44 / 38 / 32
Sound Power			H / M / L dBA	48 / 44 / 39	48 / 44 / 39	54 / 48 / 42
Dimensions			Body W x H x D mm	600 X 600 X 146	600 X 600 X 146	600 X 600 X 146
Net Weight			kg	15.0	15.0	15.0
Piping Connection	Liquid		mm	6.35	6.35	6.35
	Gas		mm	12.7	12.7	12.7
	Drain	I.D	mm	12.2	12.2	12.2

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero









- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D : ' Internal Diameter '

Accessories

Model		ARNU07GSF14	ARNU09GSF14	ARNU12GSF14
Dry Contact	Simple (1 Contact Point with Case)		PDRYCB000	
	2 Contact Point		PDRYCB400	
	For Thermostat (On-Off / Mode / Fan Speed)		PDRYCB300	
	Modbus Communication		PDRYCB500	
EEV Kit for MULTI V Indoor			PRGK024A0	

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
							
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCL0Q (Black) PQRCVCL0QW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB