

INDOOR UNIT SPECIFICATION

STANDARD

ARNU05GSJC4 / ARNU07GSJC4 / ARNU09GSJC4 / ARNU12GSJC4 / ARNU15GSJC4
ARNU18GSKC4 / ARNU24GSKC4 / ARNU30GSVA4 / ARNU36GSVA4

INDOOR UNIT



Model	Independent Unit	ARNU05GSJC4	ARNU07GSJC4	ARNU09GSJC4	ARNU12GSJC4	ARNU15GSJC4	ARNU18GSKC4	ARNU24GSKC4	ARNU30GSVA4	ARNU36GSVA4
Capacity	Cooling Nom kW	1.6	2.2	2.8	3.6	4.5	5.6	7.1	8.5	10.4
	Heating Nom kW	1.8	2.5	3.2	4.0	5.0	6.3	7.5	9.2	10.8
Power Input	Cooling / Heating Nom ¹⁾ W	10.0	11.0	12.0	15.0	23.0	32.0	39.0	83	98
	Cooling / Heating Rated ²⁾ W	30.0	30.0	30.0	30.0	30.0	53.0	53.0	154	154
Power Supply	Ø/V/Hz	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60	1/220-240/50 1/220/60
Airflow Rate	Cooling H/M/L m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9	8.5 / 7.8 / 6.8	10.5 / 9.5 / 6.8	14.0 / 12.0 / 10.5	15.2 / 12.7 / 10.5	22.0 / 19.0 / 16.0	27.0 / 24.0 / 20.0
	Heating H/M/L m ³ /min	6.8 / 6.5 / 5.9	7.2 / 6.8 / 5.9	7.8 / 7.2 / 5.9	8.5 / 7.8 / 6.8	10.5 / 9.5 / 6.8	14.0 / 12.0 / 10.5	15.2 / 12.7 / 10.5	22.0 / 19.0 / 16.0	27.0 / 24.0 / 20.0
Sound Pressure	H/M/L dBA	30 / 29 / 28	32 / 30 / 28	34 / 32 / 28	37 / 34 / 30	42 / 39 / 32	43 / 39 / 34	46 / 41 / 34	48 / 45 / 42	50 / 47 / 43
Sound Power	H/M/L dBA	54 / 53 / 52	54 / 53 / 52	55 / 54 / 52	55 / 54 / 53	58 / 56 / 54	63 / 57 / 52	65 / 60 / 54	61 / 58 / 55	63 / 60 / 57
Dimensions Body	WxHxD mm	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189	837 x 302 x 189	998 x 330 x 210	998 x 330 x 210	1,190 x 346 x 265	1,190 x 346 x 265
Net Weight	kg	8.5	8.5	8.5	8.5	8.5	12.2	12.2	19.0	19.0
Piping Connection	Liquid mm	6.35	6.35	6.35	6.35	6.35	6.35	9.52	9.52	9.52
	Gas mm	12.7	12.7	12.7	12.7	12.7	12.7	15.88	15.88	15.9
	Drain I.D mm	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0	16.0

* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions









- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero
- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D : ' Internal Diameter '

Accessories

Model	ARNU05GSJC4	ARNU07GSJC4	ARNU09GSJC4	ARNU12GSJC4	ARNU15GSJC4	ARNU18GSKC4	ARNU24GSKC4	ARNU30GSVA4	ARNU36GSVA4
Simple (1 Contact Point with Case)	PDRYCB000								
Dry 2 Contact Point	PDRYCB400								
Contact For Thermostat (On-Off / Mode / Fan Speed)	PDRYCB300								
Modbus Communication	PDRYCB500								
EEV Kit for MULTI V Indoor	PRGK024A0								-

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
							
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCL0Q (Black) PQRCVCL0QW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB