

## INDOOR UNIT SPECIFICATION

# FLOOR STANDING UNIT

INDOOR UNIT

ARNU07GCE\*4 / ARNU09GCE\*4 / ARNU12GCE\*4  
ARNU15GCE\*4 / ARNU18GCF\*4 / ARNU24GCF\*4



\* A : Floor Standing with case



\* U : Floor Standing without case

Model	Independent Unit			ARNU07GCE*4	ARNU09GCE*4	ARNU12GCE*4	ARNU15GCE*4	ARNU18GCF*4	ARNU24GCF*4
Capacity	Cooling	Nom	kW	2.2	2.8	3.6	4.5	5.6	7.1
	Heating	Nom	kW	2.5	3.2	4.0	5.0	6.3	8.0
Power Input	Cooling / Heating	Nom <sup>1)</sup>	W	24	30	36	44	54	84
	Cooling / Heating	Rated <sup>2)</sup>	W	85	85	85	85	115	115
Power Supply			Ø / V / Hz	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60	1 / 220-240 / 50 1 / 220 / 60
Airflow Rate	Cooling	H / M / L	m <sup>3</sup> /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
	Heating	H / M / L	m <sup>3</sup> /min	8.5 / 7.5 / 6.5	9.5 / 8.5 / 7.5	10.5 / 9.5 / 8.5	11.5 / 10.0 / 9.5	16.0 / 14.0 / 12.0	18.0 / 16.0 / 14.0
Sound Pressure			H / M / L	dB(A)	35 / 33 / 31	36 / 34 / 32	37 / 35 / 33	38 / 37 / 35	40 / 37 / 34
Sound Power			H / M / L	dB(A)	54 / 52 / 50	55 / 54 / 52	57 / 55 / 54	59 / 57 / 55	60 / 57 / 54
Dimensions Body			W x H x D	mm	1,067 x 635 x 203 (A) 978 x 639 x 190 (U)	1,067 x 635 x 203 (A) 978 x 639 x 190 (U)	1,067 x 635 x 203 (A) 978 x 639 x 190 (U)	1,345 x 635 x 203 (A) 1,256 x 639 x 190 (U)	1,345 x 635 x 203 (A) 1,256 x 639 x 190 (U)
Net Weight <sup>3)</sup>			kg	27.0 (A) / 20.0 (U)	27.0 (A) / 20.0 (U)	27.0 (A) / 20.0 (U)	27.0 (A) / 20.0 (U)	34.0 (A) / 27.0 (U)	34.0 (A) / 27.0 (U)
Piping Connection	Liquid		mm	6.35	6.35	6.35	6.35	6.35	9.52
	Gas		mm	12.7	12.7	12.7	12.7	12.7	15.88
	Drain	I.D	mm	12.0	12.0	12.0	12.0	12.0	12.0

\* This product contains Fluorinated Greenhouse Gases. (R410A)

1) Nom. : Performance tested under EN14511

2) Rated : Max power input allowed for fan motor

Note : 1. Capacities are based on the following conditions








- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero
- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

2. Due to our policy of innovation some specifications may be changed without notification

3. I.D : ' Internal Diameter '

## Accessories

Model	ARNU07GCE*4	ARNU09GCE*4	ARNU12GCE*4	ARNU15GCE*4	ARNU18GCF*4	ARNU24GCF*4
Dry Contact	Simple (1 Contact Point with Case)			PDRYCB000		
	2 Contact Point			PDRYCB400		
	For Thermostat (On-Off / Mode / Fan Speed)			PDRYCB300		
	Modbus Communication			PDRYCB500		
EEV Kit for MULTI V Indoor			PRGK024A0			
IR Receiver			PWLRV/N000			-

Wired Remote Controller							Wireless Remote Controller
Premium	Standard III		Standard II		Simple	Simple for Hotel	
							
PREMTA000 PREMTA000A PREMTA000B	PREMTB100 (White)	PREMTBB10 (Black)	PREMTB001 (White)	PREMTBB01 (Black)	PQRCVCL0Q (Black) PQRCVCL0QW (White)	PQRCHCA0Q (Black) PQRCHCA0QW (White)	PQWRHQ0FDB